

RETAIL LIGHTING

CANYON LED

Product Description

Features interchangeable narrow, medium, wide or extra wide beam optics, as lenses (ideal for hospitality spaces) or reflectors (featuring ‘Retail Hot Spot and Halo’ for use in retail). Lens can not retrofit into a luminaire designed for reflector: specify either lens or reflector. High power, efficient COB LED gives a system efficacy of up to 105lm/W. Remote LED driver supplied with connecting leads and plugs. Primary leads supplied with industry standard 3 pole connectors as standard, for fast easy installation. Available in White (RAL 9010), Black (RAL 9005), or custom Silver as standard, and in any other RAL to special order. Supplied for recessing into plasterboard. Head rotates 355° and swings 45° either way from horizontal. Ra >80. Power factor 0.9. L80B10 to 50,000hrs. 5 year warranty.

Product Image



Product Spec

Input Voltage (Min)	220	Cutout Length (mm)	480, 320, 180
Input Voltage (Max)	240	Cutout Width (mm)	170, 180
Power Factor	0.9	Recess Depth (mm)	106
Input Voltage Type	AC	Height (mm)	106
IP Rating	IP20	Positional Adjustment	Adjustable

Dimensions

1 Light	195mm/195mm/106mm
2 Light	350mm/195mm/106mm
3 Light	510mm/195mm/106mm

Compliance & Approvals:



Models

Title	Rated power	Colour temperature	Luminous flux **	Dimensions
CANYON 1X12W	12W	2700K - 4000K	1000lm	195mm/195mm/106mm
CANYON 2X12W	12W	2700K - 4000K	2000lm	350mm/195mm/106mm
CANYON 3X12W	12W	2700K - 4000K	3000lm	510mm/195mm/106mm
CANYON 1X24W	24W	2700K - 4000K	2000lm	195mm/195mm/106mm
CANYON 2X24W	24W	2700K - 4000K	4000lm	350mm/195mm/106mm
CANYON 3X24W	24W	2700K - 4000K	6000lm	510mm/195mm/106mm
CANYON 1X38W	38W	2700K - 4000K	3000lm	195mm/195mm/106mm
CANYON 2X38W	38W	2700K - 4000K	6000lm	350mm/195mm/106mm
CANYON 3X38W	38W	2700K - 4000K	9000lm	510mm/195mm/106mm