

Product Description

Dedicated LED light source with polycarbonate diffuser. Traditional T8 batten body. Ideal for replacement/ alternative to T5/T8. Commercial / retail and domestic use. Cool white - 4000K
5 Year Warranty (Replacement only)

Product Image



Product Spec

Version	20W
Lumens (lm)	2300
Efficacy (lm/w)	115
Beam Angle °	150
CCT Temperature (k)	4000K
Running current (A)	0.173
Power Factor	>0.9
Input voltage	Mains 230V 50Hz
Construction	Metal
Lifespan (hrs)	30,000
Class	1
IP rating	IP20
Operational temperature:	-5°C to 45°C
Warranty	5 Years
Dimmable	No

Version	26W
Lumens (lm)	3000
Efficacy (lm/w)	115
Beam Angle °	150
CCT Temperature (k)	4000K
Running current (A)	0.126
Power Factor	>0.9
Input voltage	Mains 230V 50Hz
Construction	Metal
Lifespan (hrs)	30,000
Class	1
IP rating	IP20
Operational temperature:	-5°C to 45°C
Warranty	5 Years
Dimmable	No

Version	30W
Lumens (lm)	3450
Efficacy (lm/w)	115
Beam Angle °	150
CCT Temperature (k)	4000K
Running current (A)	0.147
Power Factor	>0.9
Input voltage	Mains 230V 50Hz
Construction	Metal
Lifespan (hrs)	30,000
Class	1
IP rating	IP20
Operational temperature:	-5°C to 45°C
Warranty	5 Years
Dimmable	No

Dimensions & Certifications

Interno I 20W	1225 (L) x 60 (W) x 85 (D)
Interno I 26W	1525 (L) x 60 (W) x 85 (D)
Interno I 30W	1790 (L) x 60 (W) x 85 (D)

