

Product Description

A range of highly efficient and economical T8 LED Tubes. They are available in standard lengths of two to six foot and stocked in 4000K colour temperatures. LED Fuse to be ordered separately if required (magnetic ballasts). Supplied individually packed in cardboard sleeves. Wired live & neutral to one end

Product Image



Product Spec

|                         |                    |
|-------------------------|--------------------|
| Version                 | 18W                |
| Shape / Type            | Tube               |
| Material                | Polycarbonate tube |
| CCT Temperature (k)     | 4000               |
| Guarantee               | 3 Years            |
| Life Expectancy (hours) | 25,000             |
| Lumen Output            | 1700lm             |
| Working Temperature     | -20 - 40°C         |
| Power Factor            | >0.9               |
| Beam Angle              | 180°               |
| RA                      | 80                 |

|                         |                    |
|-------------------------|--------------------|
| Version                 | 22W                |
| Shape / Type            | Tube               |
| Material                | Polycarbonate tube |
| CCT Temperature (k)     | 4000               |
| Guarantee               | 3 Years            |
| Life Expectancy (hours) | 25,000             |
| Lumen Output            | 2100lm             |
| Working Temperature     | -20 - 40°C         |
| Power Factor            | >0.9               |
| Beam Angle              | 180°               |
| CRI                     | 80                 |

|                         |                    |
|-------------------------|--------------------|
| Version                 | 26W                |
| Shape / Type            | Tube               |
| Material                | Polycarbonate tube |
| CCT Temperature (k)     | 4000               |
| Guarantee               | 3 Years            |
| Life Expectancy (hours) | 25,000             |
| Lumen Output            | 2400lm             |
| Working Temperature     | -20 - 40°C         |
| Power Factor            | >0.9               |
| Beam Angle              | 150°               |
| CRI                     | 80                 |

Dimensions & Certifications

|           |                     |
|-----------|---------------------|
| Linea 18W | 1200 (L) x 27 ( Ø ) |
| Linea 22W | 1500 (L) x 27 ( Ø ) |
| Linea 26W | 1800 (L) x 27 ( Ø ) |

