

INDUSTRIAL LIGHTING

LYRA LED

Product Description

A multipurpose LED fitting intended for using in the areas where high dust and moisture resistance is required. Highly recommended to be used in industrial buildings (factories, laboratories), warehouses, car parks (underground and multilevel), sports stadiums, transport terminals and underground passageways. The fitting works perfectly while designing new applications as well as replacing traditional fluorescent luminaires with energy-saving LED solutions. Its construction is intended both for surface and suspended mounting.

Product Image



Product Spec

Supply voltage:	220-240V	Material of the body:	PC
Frequency:	50 – 60Hz	Colour temperature:	3000K, 4000K
Ingress protection IP:	IP66	Mounting version:	Surface / suspended
Impact resistance IK:	IK09	Material of the diffuser:	PC
Energy efficiency class:	A ++	Type of the diffuser:	Mat
Electrical protection class:	I	Light Source	LED

Dimensions

Size	1432/85/80mm
------	--------------

Compliance & Approvals:



Models

Title	Rated power	Colour temperature	Luminous flux **	Material of the diffuser	Energy efficiency class	Dimensions
LYRA 28W	28	4000K	6500lm	PC	A+	1432/85/80mm
LYRA 43W	43	3000K	6500lm	PC	A+	1432/85/80mm
LYRA 43W	43	4000K	7000lm	PC	A+	1432/85/80mm
LYRA 70W	70	3000K	10300lm	PC	A+	1432/85/80mm
LYRA 70W	70	4000K	10900lm	PC	A+	1432/85/80mm