

# INDUSTRIAL LIGHTING

# NEUS LED

## Product Description

Multi-purpose LED luminaire designed for indoor application. Especially recommended for public rooms and corridors (administration buildings, schools, universities and health care buildings). Opal diffuser secures against glare effect. Appropriate for new applications as well as replacing conventional T8 & T5 fittings for energy saving LED solutions. Fitting construction adapted for surface mounting (ceiling) using the included accessory installation kit.

## Product Image



## Product Spec

<b>Supply voltage:</b>	230V	<b>Material of the body:</b>	Powder coated steel
<b>Frequency:</b>	50Hz	<b>Colour temperature:</b>	3000K, 4000K
<b>Ingress protection IP:</b>	IP40	<b>Colour of the body:</b>	White
<b>Rated power:</b>	40W-60W	<b>Mounting version:</b>	Surface
<b>Electrical protection class:</b>	I	<b>Material of the diffuser:</b>	PMMA
<b>Type of the diffuser:</b>	PRM, PRM MAT		

## Dimensions

<b>Size</b>	1558/161/68mm
-------------	---------------

## Compliance & Approvals:



## Models

Title	Rated power	Colour temperature	Luminous flux **	Material of the diffuser	Type of the diffuser	Dimensions
Neus 40W	40W	3000K	3600lm	PMMA	PRM MAT	1558/161/68mm
Neus 40W	40W	4000K	3900lm	PMMA	PRM MAT	1558/161/68mm
Neus 40W	40W	3000K	4300lm	PMMA	PRM	1558/161/68mm
Neus 40W	40W	4000K	4650lm	PMMA	PRM	1558/161/68mm
Neus 60W	60W	3000K	5200lm	PMMA	PRM MAT	1558/161/68mm
Neus 60W	60W	4000K	5600lm	PMMA	PRM MAT	1558/161/68mm
Neus 60W	60W	3000K	6350lm	PMMA	PRM	1558/161/68mm
Neus 60W	60W	4000K	6800lm	PMMA	PRM	1558/161/68mm